

(19) World Intellectual Property Organization
International Bureau



PCT

(43) International Publication Date
26 May 2006 (26.05.2006)

(10) International Publication Number
WO 2006/054828 A1

(51) International Patent Classification:
B04B 5/02 (2006.01)

(21) International Application Number:
PCT/KR2005/003065

(22) International Filing Date:
15 September 2005 (15.09.2005)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2004-0094893
19 November 2004 (19.11.2004) KR

(71) Applicant (for all designated States except US): **HANLAB CORPORATION** [KR/KR]; 484-1, Dongpae-ri, Gyohaeup, Paju-si, Gyeonggi-do 413-833 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KIM, Hak Chul** [KR/KR]; 1512-103, Hanareum Apt., Sang 1-dong,

Wonmi-gu, Bucheon-si, Gyeonggi-do 420-752 (KR).
PARK, Chong Tae [KR/KR]; 457-19, Shillim 4-dong, Kwanak-gu, Seoul 151-014 (KR).


(74) Agent: **NAM, Sang-Sun**; KAL Bldg., 3rd Floor, 41-3 Seosomun-Dong, Jung-Gu, Seoul 100-813 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,

[Continued on next page]

(54) Title: **AUTOMATIC BALANCING CENTRIFUGAL APPARATUS BY FLUID COMPENSATION**



(57) Abstract: The invention relates to an automatic balancing centrifugal apparatus by fluid compensation, which compensates a load imbalance among buckets holding samples by injecting a fluid into the buckets or sucking the fluid from the buckets, thereby simplifying the overall structure of the centrifugal apparatus, increasing the durability, and centrifuging a large quantity of samples under various high-speed rotation conditions smoothly. The automatic balancing centrifugal apparatus by fluid compensation comprises: rotors on which a plurality of buckets are mounted; a centrifuge motor for rotating said rotors; a load measurement mechanism, which is installed so as to lift and lower along the rotation trace of said buckets and which measures the load of said buckets while the restraint of the buckets is being released at the time of lifting; a position sensing mechanism for sensing whether or not each of said buckets is positioned right above said load measurement mechanism; a fluid compensation mechanism for injecting a fluid into said buckets or for sucking the fluid from the buckets; and a main control part for controlling the overall operations of each of said elements and for controlling said fluid compensation mechanism so that the loads of said buckets can become equal to each other.

WO 2006/054828 A1



RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.